


Playa Model



Features - Summary Description

Lightweight for rooftop and pedestrian walkway applications. Tight voidspace to allow for ideal foot traffic and average permeability.

Physical Specification

| | |
|--------------------------------|---------------|
| Dry Weight KG | 2.85 |
| Dimensions Cm | 4.8 x 4.8 x 6 |
| Block Count | 25 |
| Total Coverage Cm ² | 29 |
| Physical Dimension Cm | 27 |

Installation Specifications

| | |
|----------------------------------|---------------|
| Pavers per Sq Meter | 13.22 |
| Gap Space Cm | 01 |
| Void Space Cm ³ | 507 |
| Romex Filler Grams | 1100 |
| Total Pavers Per Pallet | 288 |
| Pallet Weight KG | 450 |
| Pallet Dimensions cm (W x L x H) | 90 x 120 x 94 |

Material Specification (Wood)

COMMON NAME

BLACK LOCUST

| | | | |
|------------------------|-----------------------------|---------------------------|-------------------------------|
| Color | Blonde to light red/brown | Modulus of Elasticity | 2,050,000 lbf/in ² |
| Scientific Name | Robinia Pseudoacacia | Radial Movement | 4.60% |
| Grain | Tight Grain | Tangential Movement | 7.20% |
| Density @ 12% Moisture | 4.26 pounds per Brd Ft | Volumetric | 10.20% |
| Janka Hardness | 1700 | T/R Ratio | 1.60 |
| Modulus of Rupture | 19,400 lb/inch ² | Maximum Crushing Strength | 10,200 lbf/inch ² |

Environmental Benefits

Carbon Sequestered Per Paver 1.8 kg Carbon



BIOFILTRATION



STORMWATER MANAGEMENT



HEAT ISLAND EFFECT



CHEMICAL FREE

Product Benefits



WARRANTY



PET FRIENDLY



ROT RESISTANT



FROST RESISTANT



PERMEABILITY